

Phase & Voltage Protection Relay



- VP005-1 220V รหัส TC108 ราคา 1,380 บาท
- VP005-3 220V รหัส TC109 ราคา 1,440 บาท
- VP005-3 380V รหัส TC113 ราคา 1,440 บาท

ขนาดหน้าปัด 17.6 x 90 มม. ลึก 65 มม. ยึดราง 35 มม.
ระบบตรวจจับ 220V AC , 1 เฟส/ 2 สาย (VP005-1)
ระบบตรวจจับ 220V AC , 3 เฟส/ 3 สาย (VP005-3)
ระบบตรวจจับ 380V AC , 3 เฟส / 3 สาย (VP005-3)
การทำงาน
- ทำงานเมื่อแรงดันไฟฟ้า ตก/เกิน
- ทำงานเมื่อไฟขาดเฟส หรือ ไฟสลับเฟส
- ปกติ = ไฟเขียว,ไฟแดง ติด, Over = ไฟแดงติด , Under = ไฟเขียวติด
ขาดเฟส = ไฟไม่ติดเลย หรือไฟเขียวติด , สลับเฟส = ไฟเขียวติด

Spec.



PV Surge protector 2P 1000V DC



รหัส SP901
ราคา 1,780 บาท

Model	SSPD DC
Max continuous operating voltage U _c (V)	1000
Nominal discharge current I _n (kA)	20
Max discharge current I _{max} (kA)	40
Voltage protection level up (kV)	<<3.2
Response time (ns)	<25
Min.Sectional area of incoming wire L/N (mm ²)	4
Min.Sectional area of incoming ground wire PE (mm ²)	6
Fuse or circuit breaker selection (A)	32
Installation	35mm standard DIN Rail
Working temperature	-40°C ~+85°C
Inducation window	Normal : green Failure : red

