

Digital Meter 48x48 SAZN



Digital Meter 72x72 SAZN



Power Meter
96x96

Meter	เฟส	Range	48x48	72x72	96x96	ราคา
			รหัส	รหัส	รหัส	
3Amp	3P	Direct measurement : AC 0-10A Accessory device : AC 0-9999A(CT*/5A)	MT238	MT231		2,450
3Volt	3P	Direct measurement : (48x48) AC 0-220V, (72x72) AC 0-600V Accessory device : AC 0-9999KV(PT*/100V)	MT239	MT232		
Amp+Volt+Hz	1P	Volt. Direct measurement : AC 0-600V Accessory device : AC 0-9999KV(PT*/100V) Amp. Direct measurement : AC 0-10A Accessory device : AC 0-9999A(CT*/5A) Hz. 45-65 Hz	MT240	MT233		
Power Factor (COS)	1P	0.000C-0.500C-1.000-0.000L-0.500L	MT241	MT234		
Hz (Frequency)	1P	45-65 Hz	MT242	MT235		1,300
Amp	1P	Direct measurement : AC 0-5A Accessory device : AC 0-9999A (CT*/5A)		MT236		
Volt	1P	AC 0-600V		MT237		
Power Factor Amp+Volt+Hz+ PF+Kw+kWh ต้องตั้งค่า 3P3W หรือ 3P4W และตั้งค่า CT	3P/4W	Signal input:voltage:AC 100V,400V ;current:AC 1A,5A;frequency:45~65Hz Auxiliary:AC 220V + 10%,50/60Hz Communication interface:RS485 serial communication, applying MODBUS_RTU Pulse constant:3200imp/kWh or 3200imp/kVarh	Model : SFD-9SY-E		MT291	6,000
			Model : SFS-9SY-3E		MT293	3,200