

ลูกเซอร์กิต เบรกเกอร์ C-45 และ C-60



1P 12 pcs/box
2P 6 pcs/box
3P 4 pcs/box

AMP	1P รหัส	1P ราคา	2P รหัส	2P ราคา	3P รหัส	3P ราคา
2A	CB299	130	-	-	-	-
4A	CB300		-	-	-	-
6A	CB304		CB319	244	CB321	366
10A	CB301	122	CB316		CB322	
16A	CB310		CB317		CB323	
20A	CB305		CB311		CB324	
25A	CB306		CB318		CB325	
32A	CB303		CB312	260	CB326	390
40A	CB307		CB313		CB327	
50A	CB308	130	CB314		CB328	
63A	CB309		CB320		CB329	



1P 12 pcs/box
2P 6 pcs/box
3P 4 pcs/box

AMP	1P รหัส	1P ราคา	2P รหัส	2P ราคา	3P รหัส	3P ราคา
2A	CB361	250	-	-	-	-
4A	CB362		-	-	-	-
6A	CB363		CB372	400	CB381	600
10A	CB364	200	CB373		CB382	
16A	CB365		CB374		CB383	
20A	CB366		CB375		CB384	
25A	CB367		CB376		CB385	
32A	CB368		CB377	500	CB386	750
40A	CB369	250	CB378		CB387	
50A	CB370		CB379		CB388	
63A	CB371		CB380		CB389	

Specification

		C-45 Series		C-60 Series	
		1P	2P & 3P	1P	2P & 3P
Rated Voltage		240V	415V	240V	415V
Interupting	2A - 40A	6KA (240V)	6KA (415V)	10KA (240V)	10KA (415V)
Capacity	50A - 63A	4KA (240V)	4KA (415V)	10KA (240V)	10KA (415V)



Spec.

เบรกเกอร์ DC1000V 2P



6 Pcs / Box

AMP	SUNPULSE (CARSPA)		SAZN (NEW)	
	รหัส	ราคา	รหัส	ราคา
2P 16A	CB265	1050	CB275	230
2P 20A	CB266		CB276	
2P 25A	CB267		CB277	
2P 32A	CB268		CB278	250
2P 40A	CB269		CB279	
2P 50A	CB270		CB280	
2P 63A	CB271		CB281	

The number of poles	2P
Rated Voltage (V)	DC500V/DC1000V
Rated Current In (A)	16, 20, 32
Rated short circuit capacity Icn(KA) (T=4ms)	6
Instantaneous release form	B type/C type
Rated impulse withstand voltage Uimp (KV)	4
Rated insulation voltage	1200
Life (time)	with a load of 10000 times, not with a load of 20000 times
Use environment	minus 25-40 ambient temperature
Can take accessories	auxiliary switch, alarm switch, shunt
Maximum wiring capacity	25mm ²