



CS-360TRD

รหัส MM009 ราคา 750 บาท

Function	Full scale value	Accuracy	Remarks
DCV ---	0.1	± 5% against full scale	Input impedance 20k Ω/V
	0.25/2.5/10/50	± 3% against full scale	
	250/1000	± 3% against full scale	Input impedance 9k Ω/V
ACV ~	10/50/250/1000	± 4% against full scale	Input impedance 9k Ω/V 30Hz~100kHz wilhin ± 3%f.s (AC10V RANGE)
DCA ---	50 μ	± 3% against full scale	•1 Voltage drop 0.1V
	2.5m/25m/0.25	± 3% against full scale	•1 Voltage drop 0.25V
Ω	2k/20k/2M (X1/X10/X1K)	± 3% of arc	Center value 20Ω Max. value 2kΩ Release voltage 3V
	200M (X100k)	± 5% of arc	
C	10 μ F	---	•2
dB	-10dB ~ +22dB (FOR 10VAC) ~ + 62dB	---	
L1	0 ~150mA atX 1 range 0 ~15mA altX 10 range 0 ~150 μ A at X 1k range 0 ~1.5 μ A altX 100k range		Current across lest pins
Use the optional probe			
HV (DC high volt)	DC 25kV		
hFE	1000 atx10 range		HFE-6T probe



สายวัดสำหรับมัลติมิเตอร์
รหัส MM014 ราคา 50 บาท



Spec.

- 1 Not including the resistance of the fuse.
- 2 Pointer indication of the maximum move by charged current in the capacitor.



DT3266F

RD290B

MM021 DT3266F ราคา 1,100-

MM022 RD290B ราคา 1,500-

ไม่แถมแบตเตอรี่

DT3266F

Function	Measuring Range	Accuracy
DCV	600V	± (0.8% +2)
ACV	500V	± (1.2% +5)
ACA	20A/200A/400A	± (1.5% +5)
OHM	200Ω /20KΩ	± (1% +2)
Size / weight	160mm x 60mm x 30mm	

RD290B

Function	Measuring Range	Accuracy
DCV	500V	± (0.8% +2)
ACV	500V	± (1.2% +5)
ACA	2000mA/20A/200A/600A	± (2.5% +5)
OHM	2000Ω	± (1% +2)
Size / weight	155mm x 44mm x 22mm	