

AUTOMATIC TRANSFER SWITCH (ATS)

Manual Changeover Switch

รุ่น WN3

Model		W-N3	
Insulation voltage		AC690V	
Rated voltage		AC380V/400V (AC660V/690V DC 125V/250V)	
Rated current (Ie)		630A~800A	
Kind of throw Double throw		Double throw	
Wiring method		Panel back (panel front is product for special order)	
Number of poles		3P	
Weight (kg)		33	
Operating current (A)	DC110V/125V	12	
	AC110V/110V	12	
	AC220V/220V230V	6	
Trip coil current (A)	DC110V/125V	4A	
	AC100V/110V	4A	
	AC200V/220V230V	2A	
	Short-time withstand current	25kA	
	Rated Conditional Short-circuit current	55kA	
	Switching capacity	AC-33B(10 le making/10 le breaking) cos ϕ = 0.35 DC-330B 1.1 le making/1.1 le breaking L/R = 1ms	
Performance	Transfer time	Power Making	100ms
		A Side Breaking	30ms
		Power Making	135ms
		B Side Breaking	30ms
	Life		Electrical : 2000 Operations, Mechanical : 6000 Operations
	Switching frequency		120 Operations/hours
Auxiliary switch		Both power A, B side are 2 normally open , 2 normally closed:	
		Switching capacity AC: 100V/110V 5A AC200V/220V 2.5A DC: 100V 0.5A	
accessories		Manual handle	

เซ็นโอเวอร์สวิตช์



- Spec.


- AT501

W2R ON-ON 3P 63A(auto/manual)

ราคา 5,500
- AT502

W2H ON-ON 3P 125A(auto/manual)

ราคา 13,500
- AT503

W2H ON-ON 3P 250A(auto/manual)

ราคา 20,000

