

Switch Power Supply

HS-Series
RU Compact



HS-25



HS-35



HS-50



HS-150

	รุ่น	HS-150-12	HS-150-24	HS-50-12	HS-50-24	HS-35-12	HS-35-24	HS-25-12	HS-25-24
	รหัส	SS315	SS308	SS313	SS314	SS311	SS312	SS316	SS309
	ราคา	1945	1945	1110	1110	945	945	800	800
Output	DC voltage	12V	24V	12V	24V	12V	24V	12V	24V
	Rated current	12.5A	6.5A	4.2A	2.1A	3A	1.5A	2.1A	1.1A
	Rated power	150W	156W	50.4W	50.4W	36W	36W	25.2W	26.4W
	Ripple&noise	100mvp-p	150mvp-p	120mvp-p	120mvp-p	120mvp-p	120mvp-p	100mvp-p	150mvp-p
	DC voltage ADJ.range	±10%	±10%	±10%	±10%	±10%	±10%	±10%	±10%
Input	Voltage range					170~264VAC, 235~373VDC			
	Frequency					47~63Hz			
	AC current	1.6A/230VAC		0.65A/230VAC		0.45A/230VAC		0.35A/230VAC	
	Efficiency	83%	85%	80%	82%	76%	78%	78%	80%
	Inrush current				cold start current 30A/230VAC				
Protection	Leakage current	< 3.5mA/240VAC		< 1mA/240VAC				< 0.5mA/240VAC	
	Overload			above 115%~135% rated power				above 110%~135% rated power	
				protection type: hiccup mode, auto-recovery after fault condition is removed				protection type: part layer type current limit,auto-recovery after fault condition is removed	
	Over voltage	15.6~17.8V	30.6~33.2V						
Others	protection type : shutoff O/P, auto-recovery after fault condition is removed								
	Dimension	159*97*38mm (L*W*H)		111*78*36mm (L*W*H)		84*58*38mm (L*W*H)		84*58*38mm (L*W*H)	
	Weight/packing	0.54kg		0.26kg		0.17kg		0.15kg	

MS-Series

SAZN



รหัส	รายการ	ราคา
SS341	MS-25 25 watt 12 volt	465
SS342	MS-25 25 watt 24 volt	
SS347	MS-35 35 watt 5 volt	500
SS343	MS-35 35 watt 12 volt	
SS344	MS-35 35 watt 24 volt	720
SS348	MS-50 50 watt 5 volt	
SS345	MS-50 50 watt 12 volt	
SS346	MS-50 50 watt 24 volt	

รหัส	รายการ	ราคา
SS349	MS-100 100 watt 5 volt	865
SS350	MS-100 100 watt 12 volt	
SS351	MS-100 100 watt 24 volt	985
SS353	MS-150 150 watt 12 volt	
SS354	MS-150 150 watt 24 volt	1,355
SS356	MS-250 250 watt 12 volt	
SS357	MS-250 250 watt 24 volt	

Adaptor



รายการ	รหัส	ราคา
24 V DC 1200mA	SS456	600
24 V DC 2000mA	SS453	790
24 V DC 3000mA	SS455	1000