




Ø16 CONTROL UNIT



SPECIFICATIONS

RATED VOLTAGE(max)		250V AC/DC		
ACI DUTY max A		3A		
RATED WORKING VOLTAGE	RATED WORKING CURRENT			
	AC		DC	
	INDUCTIVE LOAD	RESISTIVE LOAD	INDUCTIVE LOAD	RESISTIVE LOAD
24V	XX	XX	0.7A	1.0 A
110V	0.7A	1.0A	0.1A	0.2A
220V	0.5A	0.5A	XX	XX
AMBIENT TEMPERATURE		-25°C ~ 55°C		

TYPE	SPECIFICATIONS		
TYPE A 	ILLUMINATED PUSHBUTTON	PUSH LOCK ILLUMINATED PUSHBUTTON	PILOT LIGHT
	ITEM NO.		
	LAL16S	LAL16Z	LAL16D
	BULB SPECIFICATIONS		
TYPE B 	AC 110V; 220V NEON BULB		
	CONTACT CONFIGURATION		
	1A1B1C	::::	
	2A2B2C	::::	
TYPE C 	RED; YELLOW; BLUE; GREEN; WHITE		
	MECHANICAL DURABILITY(TIMES)		
	1,000,000	100,000	::::
	ELECTRICAL DURABILITY		
	100,000	50,000	::::

DIMENSIONS(mm)

